

TECHNICAL DATA

TYRE SIZE	PROFILE	PR	TYPE	RIM WIDTH	INFLATION PRESSURE	OVERALL DIAMETER	OVERALL SECTION WIDTH	REFERENCE LOAD (kg)	STATIC LOAD CAPACITY ETRTO (kg)	SET WEIGHT	
					ETRTO (bar)	(mm) ±2%	(mm) ±2%	25 km/h		(kg)	
4.00-8*	NEW	WL	6	TT	3.00D-8	4,25	420	110	600	905	4,5
5.00-8		SW	8	TT	3.00D; 3.75L-8	8,25	485	150	950	1435	8,1
15x4.5-8 (125/75-8)*		LT	12	TT	3.25L-8	10,00	385	122	750	1130	4,2
16x6-8 (150/75-8)		SW	18	TT	4.33R-8	10,50	420	155	1180	1780	9,0
18x7-8 (180/70-8)		SW	16	TT	4.33R-8	10,00	465	175	1650	2490	12,3
6.00-9		SW	14	TT	4.00E-9	10,50	540	170	1495	2260	13,0
21x8-9 (200/75-9)		SW	16	TT	6.00E-9	10,00	530	215	2120	3200	21,2
6.50-10		SW	14	TT	5.00; 5.50F-10	10,00	590	190	1800	2720	16,1
23x9-10 (225/75-10)		SW	20	TT	7.00F-10	10,00	585	230	2650	4000	23,3
7.00-12		SW	16	TT	5.00S-12	10,00	675	200	2240	3380	22,3
23x10-12 (250/60-12)		SW	22	TT	8.00G-12	10,50	600	260	2985	4510	30,3
27x10-12 (250/75-12)		SW	20	TT	8.00G-12	10,00	695	270	3550	5360	33,6
7.00-15		SW	16	TT	5.00; 5.50-15	10,00	740	205	2725	4115	24,5
7.50-15		SW	16	TT	5.00; 6.00; 6.50-15	10,00	785	225	3000	4530	27,7
28x9-15 (225/75-15)		SW	16	TT	7.0-15	10,50	715	220	3090	4665	27,1
32x12.1-15		SW	24	TT	9.75-15	10,30	810	325	4835	7300	64,7
8.25-15		SW	18	TT	6.0; 6.5; 7.0-15	9,25	840	255	3650	5510	43,2
250-15 (250/70-15)		SW	20	TT	7.0; 7.5-15	10,00	735	245	3875	5850	36,4
300-15 (315/70-15)		SW	20	TT	8.0-15	9,00	820	280	5000	7550	56,5
28x12½-15 (355/45-15)		SW	24	TT	9.75-15	10,50	710	305	3730	5630	45,4
9.00-20		LT	14	TT	7.00-20	7,60	1034	259	4500	6795	48,5
10.00-20		SW	20	TT	7.0; 7.50; 8.0-20	10,00	1070	290	5320	8035	103,5
12.00-20		SW	20	TT	8.00; 8.50; 9.00-20	10,00	1145	320	6900	10420	103,5

* Only tyre and tube without flap.